Attorney Docket No.: 500.40501X00 Serial No.: 09/931,250

speed-increasing circuit coupled between a first node and a second node, said first

node being at an input terminal of the driver circuit and said second node being in a

vicinity of an input terminal of one of the gate circuits coupled to an end of the first

wiring.--

--17. The semiconductor integrated circuit device as claimed in claim 16,

wherein the speed-increasing circuit includes a PMOS transistor .--

--18. The semiconductor integrated circuit device as claimed in claim 16,

wherein the speed-increasing circuit includes an NMOS transistor and a buffer circuit

is inserted at an input side of the second wiring .--

--19. The semiconductor integrated circuit device as claimed in claim 16,

wherein the speed-increasing circuit includes a CMOS inverter having a PMOS

transistor and an NMOS transistor .--

--20. The semiconductor integrated circuit device as claimed in claim 16,

wherein a plurality of speed-increasing circuits are additionally inserted between an

intermediate position of the second wiring and the vicinity of the input terminal of the

gate circuit connected to a position corresponding to the intermediate position.--

2

Attorney Docket No.: 500.40501X00 Serial No.: 09/931,250

--21. The semiconductor integrated circuit device as claimed in claim 16, wherein a plurality of buffer circuits are inserted at the input side of the second wiring.--

Chy,

- --22. The semiconductor integrated circuit device as claimed in claim 16, wherein a buffer circuit is inserted at the input side of the second wiring.--
- --23. The semiconductor integrated circuit device as claimed in claim 16, wherein the input signal is realized by a word line selecting signal; the driver circuit is realized by a word line driver; the first wiring is realized by a word line; and the gate circuits are realized by memory cells.--
- --24. The semiconductor integrated circuit device as claimed in claim 16, wherein the input signal is realized by a clock input signal; the driver circuit is realized by a clock driver; and the gate circuits are realized by flip-flop circuits.--